

# ArXtor Lite /Appliance Specifications

|                                       | ArXtor1000                              | ArXtor4000         | ArXtor7000       |
|---------------------------------------|-----------------------------------------|--------------------|------------------|
| Library characteristics:              |                                         |                    |                  |
| Capacity TB (BDXL 100GB Media)        | 1.5 – 10.5                              | 14.5-37            | 51-66            |
| Number of drives                      | 1-2                                     | 2-6                | 2 – 10           |
| Total # of Media Slots**              | 15-105                                  | 145-370            | 510-600          |
| SmartPacks (removable 15-discs)       | 3 / 4                                   | 4                  | 4                |
| Avg. media exchange times (seconds)   | 2                                       | 4                  | 6                |
| Automation connectivity               | iSCSI                                   |                    |                  |
| Drive connectivity                    | iSCSI                                   |                    |                  |
| Media formats                         | BDXL-R,BD-ROM, BD-R, BD-RE, DVD, CD     |                    |                  |
| Media capacity                        | Up to 100GB                             |                    |                  |
| Media characteristics                 | 120 mm Single Sided Hard Coated Surface |                    |                  |
| Software support:                     |                                         |                    |                  |
| Support for Windows and Linux         |                                         |                    |                  |
| Through 3rd party management software |                                         |                    |                  |
| Net dimensions + weight:              |                                         |                    |                  |
| Width without stands                  | 290mm / 11.5"                           | 385mm / 15.2"      | 385mm / 15.2"    |
| Width with stands                     | n/a                                     | 535mm / 21.1"      | 840mm / 33.1"    |
| Height                                | 451mm/17.8" (11U)                       | 1020mm/40.2" (23U) | 1547mm/61" (35U) |
| Depth                                 | 730mm / 28.7"                           | 705mm / 27.8"      | 705mm / 27.8"    |
| Weight (without media)                | 30kg / 66lbs                            | 70kg / 154lbs      | 110kg / 242lbs   |
| Shipping dimensions:                  |                                         |                    |                  |
| Palleted size + height (millimetres)  | 1200x800x750                            | 1200x800x1300      | 1200x800x1750    |
| Palleted size + height (inches)       | 48x32x30                                | 48x32x51           | 48x32x69         |
| Weight                                | 40 kg /88 lbs                           | 90 kg / 154 lbs    | 135 kg / 297 lbs |
| Power consumption:                    |                                         |                    |                  |
| Average (watts)                       | 120                                     | 180                | 240              |
| Peak (watts)                          | 180                                     | 450                | 920              |

**Power supply (autoswitching):**

|           | Redundant     | Redundant     | Redundant     |
|-----------|---------------|---------------|---------------|
| Voltage   | 100 – 220 VAC | 100 – 220 VAC | 100 – 220 VAC |
| Frequency | 50/60 Hz      | 50/60 Hz      | 50/60 Hz      |
| Current   | 4 -8 Amps     | 4 -8 Amps     | 4 -8 Amps     |

**Thermal emissions in BTU's per hour:**

|         |     |       |       |
|---------|-----|-------|-------|
| Average | 410 | 615   | 820   |
| Peak    | 615 | 1.540 | 3.140 |

**Operating Conditions:**

|                                    |                            |
|------------------------------------|----------------------------|
| Ambient temperature (external)     | 10 C – 40 C / 50 F – 104 F |
| Gradient of temperature (external) | 11 C/h or 51.8 F/h         |
| Relative humidity                  | 10% – 75% non condensing   |